## **ULTRA-SHORT THROW** INTERACTIVE PROJECTORS

EB-1450Ui/1460Ui





Connect, collaborate and share information effortlessly on a truly multi-purpose projection system. The EB-1400 series ultra-short throw interactive projectors offer a smart collaboration platform for sharing and co-authoring, whether across long distances or with multiple PCs and mobile devices to powerfully enhance your meetings and video conferences.



















Multi-PC Projection



EB-L1450Ui/1460Ui



### **ENGINEERED FOR BUSINESS**

#### **Intelligent Interactive Experience**

Intuitively control and draw with your fingers or interactive pens on high-speed interactive projections and share your interactions with PCs and mobile devices.

#### **Ease of Presentation**

Wide range of connectivity including remote desktop access presents unparalleled presentation convenience.

#### **Collaborative Meetings**

Organise more productive meetings and video conferences with quick information sharing and greater participant engagements.









EB-1450Ui/1460Ui

Create highly collaborative meetings with Epson smart interactive projector series. The interactive projector features advanced mobile device connectivity and remote desktop access and powerfully enhances video conference systems. Live drawings from the projector can be sent over a video conference for participants in other locations to view, ideal for concept sharing and corporate trainings.



#### Intelligent Interactive Experience

#### Finger-touch interactivity

Control your presentations and PC applications or navigate the modern touchscreen interface with the finger-touch enabled interactive projectors. You will be able to point, swipe, draw, pinch in/out and rotate using your fingers, even when projecting wirelessly. Simply use the interactive pens for adding notes or writing and let your fingers do the rest.



When connected via USB cable to a PC running Epson Easy Interactive Tools 4.2 software, the projector supports six fingers and two interactive pens, allowing multiple users to write simultaneously for maximum participation and collaboration. When operating as a standalone without a PC, the projector enables two fingers and two pens to write at the same time.



#### **Highly Engaging Presentations**

With the annotation of the interactive pens and support for finger touch gestures, you can easily modify your projections real time to create persuasive presentations that wow your audience.



#### **PC-less Interactive Functionality**

With this original PC-free interactive feature by Epson, you can write and draw on the projector's built-in digital whiteboard or any image projected from other non-PC sources such as document camera, blu-ray player, video conference system, tablets and smart phones. You may also control any photo slide shows loaded from a USB thumb drive.



#### **Dual Screen Seamless Interactivity**

To deliver the most immersive interactive experience, two projectors can be installed side by side to create an ultra-wide interactive panoramic screen of up to 177 inches diagonal. Write or move objects seamlessly across the dual screen with your fingers or interactive pens. With the extended interactive space, more meeting information can now be displayed for cross-referencing and you will never have to worry about limited drawing space anymore.



#### **New Interactive Pens**

The two new interactive pens are designed for high-speed writing, accurate response and long battery life. The high response speed and accuracy make drawing as instant and smooth as writing with a real marker on whiteboard. The pens can also function like a computer mouse to select, drag and double-click objects.



Both interactive pens are able to draw at the same time throughout the whole screen with its own selected colour. Fingers can select a third colour or the eraser function to work on the screen together with the pens. The pens also come with a side button for users to instantly activate various assigned functions to facilitate the most convenient annotation experience.



#### **Ease of Presentation**

#### **Remote Desktop Access**

The interactive projectors can remotely access a PC on your work desk or a desktop hosted on server using the Microsoft Remote Desktop Protocol. You can connect and control the remote desktop using your fingers and interactive pens. Now, you can project and annotate on information stored in different remote locations right from your meeting room, giving you unparalleled flexibility and convenience.



#### Miracast Screen Mirroring\*


Use Miracast to mirror your tablet or smart phone screen on the projection. You can display contents such as documents, photos and videos from your mobile devices simply through a wireless connection to the projector. No more messy cables to worry about.



\* Applicable on EB-1460Ui only.

#### **Wireless Multi-PC Projection**


Project from your laptop wirelessly using Epson EasyMP Multi PC Projection 2.0 software. Up to 50 laptops and mobile devices can connect to a single projector via this software. A laptop or device can be assigned as the moderator and send a projected image to connected clients. The moderator can also look at thumbnail previews of connected clients and select up to four of them to be projected on the screen at the same time for comparison.



#### **Ultra-short Throw Advantage**

With ultra-short throw, light from these interactive projectors is less distracting as it barely touches the presenter, ensuring a more comfortable experience compared to conventional models. As light is not blocked by the presenter, less shadow is formed on the screen, allowing the audience to clearly see the information projected at all times.

The ultra-short throw setup also ensures stable performance of the two interactive pens and provides consistent colour uniformity over the entire screen. These advantages keep the presenter more comfortable and enable clear smooth presentations.



Conventional projector with blinding glare on presenter's face

Epson ultra-short throw projector

With ultra-short throw, it is now possible to project a large screen within the narrow space of retail windows. You can now create captivating window displays with the help of large projections to increase the visibility of store merchandise. The ultra-short throw projectors can also be flexibly mounted onto a table to create an engaging interactive tabletop for meetings and discussions.



Large projection in small space of window display



Table top projection

#### **Collaborative Meetings**

#### **iProjection\* App for Mobile Devices**

The iProjection app enables both iOS and Android devices to easily connect to the projector. You can use iProjection to wirelessly project various documents, photos and web pages, and draw on the device screen and share on projection. To connect, search for the projector in your local network or simply scan a QR code displayed on the projector screen. Remote control function is also built into iProjection so you can use the app to control projector functions. In addition, iProjection now supports screen mirroring (without audio) from devices running on Android 5.0 and above.





\* In iProjection, projector profile search, multi-screen display, distribution function, audio transfer, movie file transfer, interrupt connection disabling and encryption data transfer capabilities are not supported.

#### **Interactive Whiteboard Sharing**

The in-built digital whiteboard can be shared with up to 15 laptops, mobile devices or same series interactive projectors residing in the same network. Interactive drawings and images inserted from all parties can be seen in real time by every connected user. Laptops and devices access the common shared whiteboard by using only the web browser, removing the need to install any software or apps. Images from other input sources of the projector can also be interactively shared this way with laptops and mobile devices, allowing every participant in the meeting to coauthor and actively collaborate.




#### **Digital Whiteboard Capability**

Even with no PC connected, you can enjoy up to 50 pages of digital whiteboarding by using the projector's in-built digital whiteboard mode. You can also output and share the written pages in multiple ways and formats. If a PC is connected, you can run the Epson Easy Interactive Tools 4.2 to use the whiteboard software.



#### **Microsoft Office Ink Support**

When connected to a PC (Windows Vista or later) projecting Microsoft Office documents, you can draw and write on Microsoft PowerPoint, Excel or Word documents using Microsoft Office Ink. The drawings can be saved into the documents in Microsoft Office file formats for future review or editing.



#### **Quick Information Sharing**


With the rich input-output options provided by the smart interactive projector platform, you can enjoy great flexibility of importing information from various sources and sharing the meeting results in multiple ways, saving you precious time and increasing productivity.



When the meeting is over, you may directly print the whiteboard pages or simply distribute them by email to up to 50 participants at one go. The projector is able to access Active Directory of the network to allow you to conveniently search for participants' email addresses.





Alternatively, save your images and drawings on the digital whiteboard directly to your PC by connecting the projector to your PC via USB cable or save to a USB thumb drive or network storage location. You can also directly print to USB or network printers in A3 or A4 size formats.



#### **Easy On-screen Editing and Arrangement**

Any images or writing on the screen can be resized and moved as if it were an object. You can easily rearrange and organise information on the screen to make room for more contents to be shown on the screen.





#### **DVI Video Output**

With the projector video output function, you can output the image from your interactive projector to another larger projector to duplicate the projection on a larger screen. This function is perfect for sharing your drawings or images via an interactive projector with a large audience in an auditorium.



#### **Multi-Location Interactivity**

Up to four interactive projectors in different locations can share the interactivity of the projector screen as long as they are connected to the same network, for example via VPN. This function is enabled using Epson EasyMP Multi PC Projection 2.0 software to allow you to have a collaborative meeting with participants in different locations.



#### Slide to Split Screen

Simply slide an on-screen handle to split the projector screen into two. With the maximum 100-inch large screen size, you can project images from two different sources side-by-side clearly. For example, you may show your presentation or video conference on one side and write on the digital whiteboard on the another side. With this function, there is no need to purchase two displays for your meeting room.



#### **Enhancing Video Conference Systems**

The interactive projector powerfully enhances video conference systems with interactive collaboration functions. The video conference image can be displayed on one side of the split screen while the digital whiteboard or multi-location interactive screen can be shown on the other. This allows users to see the conference video and, at the same time, draw on any PC applications like CAD or Microsoft Office documents. Participants using the multi-location function can make annotations that can be viewed by other connected parties in the conference. The video conference system can also transmit the DVI video output from the interactive projector to show remote participants live drawings and annotations, ideal for concept sharing and corporate trainings.






#### **Superior Image Quality**

#### **Beyond Full HD Resolution**

Enjoy a dynamic viewing experience with 1920 x 1200 WUXGA resolution that is beyond Full HD. Deliver clearer high-resolution image displays from PCs, tablets and smart phones and watch your photos, 3D CAD, Blu-ray and online videos come to life in Full HD. Data figures on spreadsheets and charts will also be displayed clearly for everyone to read accurately.



#### No Reflection Glare On Projection

The projection screen is not glossy and does not cause glaring reflections of ambient light like florescent lamps and sunlight from windows. The audience will not be distracted by such reflections and all information projected can be clearly seen at all times.



#### **Larger Images**

With a projection screen size of up to 100 inches, you enjoy bigger image projection for greater visibility.



#### Wide Range of Connectivity

#### **Simplify Meeting Preparations**

With the ability to send the projected image to connected laptops and mobile devices, you no longer have to prepare meeting handouts, saving time and paper.



#### **Longer Lamp Life**

With a long lamp life of 10,000 hours in ECO mode, the frequency of lamp replacements is reduced, saving you time and money, and lowering the total cost of ownership. The interactive projectors still perform at a brightness of 2,900 lumens even in ECO mode.

#### **Full Compatibility**

Advanced connectivity features mean convenient and hassle-free projections of your presentations. With a wide-ranging interface, these projections not only correspond with multiple conventional analogue sources, they are also compatible with HDMI and supports CEC. In addition, one of the two HDMI input terminals is MHL-enabled for the mirroring of Android mobile devices.

Simply connect your MHL-compatible device with the MHL cable to fully enjoy your contents on the big screen. What's more, when connected, you can charge your Android mobile device and operate it using the projector's remote control.



#### **Eco Features**

- Uses just 0.3W of power in standby mode
- Projector optics employ lead-free lenses
- Unpainted plastic housing reduces the environment impact
- The flame retardants used in the plastic housing do not contain chlorine or bromine

#### Better Products for a Better Future\*

For more information on Epson's environmental programmes, visit http://global.epson.com/SR/environment.



## SEE VIBRANT, REALISTIC COLOURS WITH HIGH COLOUR BRIGHTNESS.



See colours like never before. Epson 3LCD projectors deliver brilliant colours that match its white brightness to give you balanced, realistic, and vibrant images. It's no wonder Epson projectors are the people's preferred choice.



#### **Up to 3X Wider Colour Gamut**

Colour gamut refers to the range of colours that can be reproduced by a display device - the wider the gamut, the more realistic it is. Epson 3LCD projectors project three times wider gamut that matches closely to the original standard of a display device (sRGB), as compared to 1-chip projectors.

fly-priced leading 1-chip DLP<sup>®</sup> business and education projectors based on NPD data from July 2011 through June 2012 ppm). Colour brightness (colour light output) measured in accordance with IDMS 15.4. Actual colour brightness will vary e conditions. 3.(CP) is a registered trademark of Selixo Epson Corporation. DLP<sup>®</sup> is a registered trademark of Texas se here does not imply any affiation with or endorsement by them.



COLOUR GAMUT

Comparing the yellow corners among the three gamuts, 1-chip projectors have a distinctly darker and smaller set of colours which are not as vibrant as Epson 3LCD projectors.

COLOUR GAMUT

#### **Up to 3X Brighter Colours**

Epson 3LCD projectors deliver up to three times the colour brightness, effortlessly creating the same colour and white brightness, resulting in faithful images with superior colour balance.






#### No Rainbow Effect



With 1-chip projectors, the spinning motion of the sequential colour wheels tend to cause colours to break out into distinct red, green and blue. Called the

rainbow effect, this may cause users to suffer headaches with prolonged viewing. Epson projectors do not give out this effect, giving users a comfortable experience.





www.epson.com.sg/colourbrightness


## **EPSON 3LCD TECHNOLOGY - FOR BRIGHT, FAITHFUL COLOURS**

3LCD projectors offer brighter and more accurate colours as they produce different shades and hues by filtering, then mixing beams of the three primary colours (red, green and blue).

In a 3LCD projector, white light is first split into the three beams of primary colours. Each beam is then filtered through its own LCD that will give each individual pixel of the image its exact brightness for each colour. The colour beams are then perfectly recombined in a prism before being projected out as a complete image.

This compares to projectors using single-chip technology that actually project individual colours sequentially by filtering their single white light beam through a colour wheel, and then relying on human colour perception to combine the colours in the viewers' minds.

As a result, 3LCD projectors also offer greater detail, smoother gradations, no "colour breakup" effect, are easier on viewers' eyes, and consume about 25% less power to achieve the same brightness compared to a single-chip projector using a lamp of the same wattage.



3LCD projector: RGB are projected at the same time, which makes the single composite image easy on the eyes






# BIGGER PROJECTION. BRIGHTER FUTURE.



#### **Epson Projector**



58% of students in a classroom are unable to read content on a 70-inch flat panel display.\* This is why we've built projectors that depict larger and more immersive pictures, so that you can fully engage your audience and maximise every learning experience with exquisite detail and vibrancy. By not downsizing classroom displays to flat panels—you ensure the brightest minds of our future are not hindered by contents displayed too small and unreadable. Experience the real practical difference today.











Epson Southeast Asia



Epson Projector

Flat Panel Display



70"



100"

To find out more, visit www.epson.com.sg/displaysizematters

## PROTECT YOUR PROJECTOR. USE GENUINE LAMPS.



Don't compromise on safety – use Epson genuine lamps to avoid damaging your projector. Eliminate the risk of melting parts of your projector, as well as breaks that result in high-voltage shutdown. With a 0% failure rate even after 2,000 hours of usage – compared to 70% in non-genuine lamps – Epson genuine lamps are safer and more reliable. Choose the best possible viewing experience filled with long-lasting sharpness and colour in every projected image with Epson.





#### **GENUINE EPSON LABEL**

To ensure the best quality and safety when using your Epson Projector, look for the "Genuine EPSON Colour Shifting Label" on your projector lamp. Real quality and value, only with Epson genuine supplies.

#### **DANGERS OF NON-GENUINE LAMPS**



#### **UNRELIABLE**

Counterfeit lamps deteriorate and break much faster than genuine ones.



#### **UNSAFE**

Parts of your Epson projector such as the housing or wires may melt, disconnect, or become damaged when using non-genuine lamps.



#### **POOR IMAGE QUALITY**

Counterfeit lamps may result in inaccurate colour projection, lower brightness levels, as well as flickering images that spoil your viewing experience.

#### EB-1450Ui/1460Ui



Projection Technology		EB-1450Ui	EB-1460Ui
		RGB liquid crystal shutter projection system	
Specifications of Mair	n Parts		
_CD	Size	0.67" (D10)	
	Native Resolution	WUXGA	
Projection Lens	Type	No Optical Zoom / Focus (Manual)	
	F-Number	1.60	
	Focal Length	4.2mm	
	Zoom Ratio	1.0 - 1.35 (Digital Zoom)	
	Throw Ratio	0.27 - 0.37 (Wide to Tele)	
_amp	Type	267W UHE	300W UHE
Life (Normal / Eco)*1		5,000 / 10,000 hrs	·
Screen Size (Projecte	d Distance)	70" - 100" [40.5 - 59.3 cm]	
		90" screen 53cm	
Brightness <sup>2</sup>			
White Light Output (Nor	mal / Eco)	3,800lm / 2,900lm	4,400lm / 2,900lm
Colour Light Output		3,800lm	4,400lm
Contrast Ratio		16,000:1	
Internal Speaker(s)			
Sound Output		16W Mono x 1	
Geometric Correction			
Vertical / Horizontal Key	stone	±3°/±3°	
Quick Corner		Yes	
Connectivity			
Analog Input	D-Sub 15Pin	1 (Blue)	
	Composite	RCA x 1 (Yellow)	
Digital Input	HDMI	2 (HDMI1 in common with MHL)	
Analog Output Terminal		1 (Black)	
Digital Output Terminal	DVI-D	1 (HDCP contents are not supported)	
Audio Input	Stereo Mini Jack	2	
Audio Output	Stereo Mini Jack	1	F:
Others	USB Type A	2 (for USB Memory, Printer, USB Document Camera	
0 1 11/0	USB Type B	1 (for USB Display, Mouse, K/B, Control, Interactive,	Saving Data File to PC via Cable)
Control I/O	RS-232C	D-Sub 9pin x 1	
	Interactive Sync	ln x 1, Out x 1	
	Touch Unit Control	Mini DIN 8pin x 1	
	Remote	Stereo mini x 1 (For Control Pad)	
Network Wired LAN		RJ45 x 1 (100Mbps)	
	Wireless	Yes (ELPAP10 Included)	
Wireless Specification			
Supported Speed For E	ach Mode	IEEE 802.11b: 11Mbps <sup>13</sup>	
		IEEE 802.11g: 54Mbps <sup>*3</sup>	
_		IEEE 802.11n: 130Mbps*3	
Supported Mode		Infrastructure, Access Point	
Wireless LAN Security		Quick Mode: WPA2-PSK	
		Advanced Mode: WPA/WPA2-PSK, WPA/WPA2-E/	
		Supported EAP type: PEAP, PEAP-TLS, EAP-TLS, I	EAP-Fast, LEAP
	/n #: 1)		i e
			IEEE 000 44 (0 4011) 54441 12
		N/A	IEEE 802.11g (2.4GHz): 54 Mbps <sup>-3</sup>
		N/A	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>-3</sup>
		N/A	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>-3</sup> IEEE 802.11a (5GHz): 54 Mbps <sup>-3</sup>
		N/A	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>-3</sup> IEEE 802.11a (5GHz): 54 Mbps <sup>-3</sup> IEEE 802.11n (5GHz): 270.0 Mbps <sup>-3</sup>
Supported Speed For E		N/A	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>-3</sup> IEEE 802.11a (5GHz): 54 Mbps <sup>-3</sup>
Supported Speed For E Supported Mode	ach Mode		IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup> IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup> IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati	ach Mode		IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit	ach Mode	N/A	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology	ion	N/A Infrared	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit	ion Interactive Pen	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2)	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices	ion Interactive Pen Fingers	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers)	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con	ion Interactive Pen Fingers	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices	ion Interactive Pen Fingers	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network  Pen: Auto / Manual (25 Points)	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup> IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup> IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>
Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration	ion Interactive Pen Fingers	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points)	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration Functions	ion Interactive Pen Fingers	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network  Pen: Auto / Manual (25 Points)	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit	ion  Interactive Pen Fingers nputer	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 780Mlops <sup>3</sup>
Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensic	ion  Interactive Pen Fingers nputer	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup> IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup> IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensic Weight	ion  Interactive Pen Fingers nputer	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup> IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup> IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>
Supported Speed For E  Supported Mode  Interactive Specificati Interactive Unit Technology Input Devices  Connection To Con Calibration  Functions Touch Unit Maximum Dimensic Weight  Operating Temperatur	ion  Interactive Pen Fingers nputer	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area 51 x 210 x 95 mm 450g	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11a (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11h (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11h (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct
Supported Speed For E  Supported Mode  Interactive Specificati Interactive Unit Technology Input Devices  Connection To Con Calibration  Functions Touch Unit Maximum Dimensic Weight  Operating Temperatur	ion  Interactive Pen Fingers nputer	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm 450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use	ion  Interactive Pen Fingers nputer	N/A  Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm 450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,5005) 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%)	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi
Supported Speed For E Supported Mode Interactive Specificati nteractive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensic Weight Deparating Temperatur Single Use	ion  Interactive Pen Fingers nputer	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (0m / 0ft to 2,286m / 7,500ft)	IEEE 802.11n (2.4GHz): 130.0 Mbps³   IEEE 802.11n (5GHz): 54 Mbps³   IEEE 802.11n (5GHz): 270.0 Mbps³   IEEE 802.11n (5GHz): 270.0 Mbps³   IEEE 802.11ac (5GHz): 780Mbps³   Wi-Fi Direct
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices  Connection To Con Calibration Functions Fouch Unit Maximum Dimensic Weight Operating Temperatur Single Use Multi-projection Use	ion  Interactive Pen Fingers nputer	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network  Pen: Auto / Manual (25 Points)  Finger: Manual (16 Points)  Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft)  5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft)  5 - 36 °C <41 - 96 °F> (0m / 0ft to 2,286m / 7,500ft)  5 - 30 °C <41 - 96 °F> (0m / 0ft to 2,286m / 7,500ft)  5 - 30 °C <41 - 96 °F> (0m / 0ft to 2,286m / 7,500ft)	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E Supported Mode Interactive Specificati nteractive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Uniti-projection Use Operating Altitude	ion  Interactive Pen Fingers apputer  on (D x W x H)	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points)  Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (209 ft) 5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (209 ft) 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (209 ft) 6 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (209 ft) 0 - 3,000 m (0 - 9,842 ft) (over 1,500m / 4,921ft; wif)	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensio Weight Operating Temperatur Single Use Multi-projection Use Operating Altitude Direct Power On / Off	ion  Interactive Pen Fingers apputer  on (D x W x H)	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points)  Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) (20%  5 - 35 °C <41 - 95 °F> (ower 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (0m / 0ft to 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (ower 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 · 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 · 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 · 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 · 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 · 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 · 80 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E  Supported Mode Interactive Specificati Interactive Unit Technology Input Devices  Connection To Con Calibration  Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Multi-projection Use Direct Power On / Off Start-Up Period	ion  Interactive Pen Fingers apputer  on (D x W x H)	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °C <	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Multi-projection Use Operating Altitude Direct Power On / Off Start-Up Period Cool Down Period	ion  Interactive Pen Fingers nputer  on (D x W x H)	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network  Pen: Auto / Manual (25 Points)  Finger: Manual (16 Points)  Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 30 °C <41 - 95 °F> (over 1,286m / 7,500ft) (20% 5 - 30 °C <41 - 95 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 30 °C <41 - 86 °F> (over 1,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 1,206m / 4,921ft: wit)  Yes / N/A  About 8 seconds, Warm-up Period: 30 seconds Instant Off	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E Supported Mode Interactive Specificati nteractive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Vulti-projection Use Operating Altitude Direct Power On / Off Start-Up Period Cool Down Period	ion  Interactive Pen Fingers apputer  on (D x W x H)  re	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points)  Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 35 °C <41 - 95 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 6 - 30 °C <41 - 86 °F> (over 1,500m / 4,921ft: with Yes / N/A  About 8 seconds, Warm-up Period: 30 seconds Instant Off Electrostatic Filter	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices Connection To Con Calibration Functions Touch Unit Maximum Dimensio Weight Operating Temperatur Single Use Multi-projection Use Direct Power On / Off Start-Up Period Cool Down Period Air Filter	ion  Interactive Pen Fingers nputer on (D x W x H)  re  Type Maintenance Cycle	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (ower 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 1,500m / 4,921ft: wif) (45 / N/A)  About 8 seconds, Warm-up Period: 30 seconds Instant Off Electrostatic Filter  10,000 hour*	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E Supported Mode Interactive Specificati Interactive Unit Technology Input Devices  Connection To Con Calibration Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Multi-projection Use Direct Power On / Off Start-Up Period Cool Down Period Air Filter Power Supply Voltage	ion  Interactive Pen Fingers nputer  on (D x W x H)  re  Type Maintenance Cycle	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points)  Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 35 °C <41 - 95 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 6 - 30 °C <41 - 86 °F> (over 1,500m / 4,921ft: with Yes / N/A  About 8 seconds, Warm-up Period: 30 seconds Instant Off Electrostatic Filter	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E Supported Mode Interactive Specificati nteractive Unit Technology Input Devices Connection To Con Callibration Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Multi-projection Use Operating Altitude Direct Power On / Off Start-Up Period Cool Down Period Air Filter Power Supply Voltage Power Consumption	ion  Interactive Pen Fingers Inputer I	Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 96 °F> (over 2,286m / 7,500ft) (20% 6 - 3,000 m (0 - 9,842 ft) (over 1,500m / 4,921ft: wif Yes / N/A About 8 seconds, Warm-up Period: 30 seconds Instant Off Electrostatic Filter 10,000 hour <sup>4</sup> 100 - 240 V AC ±10%, 50/60 Hz	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11ac (5GHz): 780Mlops <sup>3</sup> IEEE 802.11ac (5GHz): 780Mlops <sup>3</sup> Wi-Fi Direct  Oft)  - 80% humidity, No condensation)  - 80% humidity, No condensation)  h high altitude mode)
Supported Speed For E Supported Mode Interactive Specificati nteractive Unit Technology Input Devices Connection To Con Callibration Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Multi-projection Use Operating Altitude Direct Power On / Off Start-Up Period Cool Down Period Air Filter Power Supply Voltage Power Consumption	ion  Interactive Pen Fingers Inputer I	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points)  Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) (20%  5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 9	IEEE 802.11n (2.4GHz): 130.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 54 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 270.0 Mbps <sup>3</sup>   IEEE 802.11n (5GHz): 780Mbps <sup>3</sup>   IEEE 802.11ac (5GHz): 780Mbps <sup>3</sup>   Wi-Fi Direct   Wi-Fi
Supported Speed For E  Supported Mode Interactive Specificati Interactive Unit Technology Input Devices  Connection To Con Calibration  Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Multi-projection Use Direct Power On / Off Start-Up Period Cool Down Period Air Filter Power Consumption I Lamp On (Normal / Eco Standby (Network On / C)	ion  Interactive Pen Fingers nputer  on (D x W x H)  re  Type Maintenance Cycle (220 - 240V) ) Off)	Infrared Digital Pen (Easy Interactive Pen 1 & 2) Yes (Up to 6 Fingers) USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 96 °F> (over 2,286m / 7,500ft) (20% 6 - 3,000 m (0 - 9,842 ft) (over 1,500m / 4,921ft: wif Yes / N/A About 8 seconds, Warm-up Period: 30 seconds Instant Off Electrostatic Filter 10,000 hour <sup>4</sup> 100 - 240 V AC ±10%, 50/60 Hz	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11ac (5GHz): 780Mlops <sup>3</sup> IEEE 802.11ac (5GHz): 780Mlops <sup>3</sup> Wi-Fi Direct  Oft)  - 80% humidity, No condensation)  - 80% humidity, No condensation)  h high altitude mode)
Input Devices  Connection To Con Calibration  Functions Touch Unit Maximum Dimensic	ion  Interactive Pen Fingers nputer  on (D x W x H)  re  Type Maintenance Cycle (220 - 240V) ) Off)	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points)  Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) (20%  5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20%  5 - 30 °C <41 - 9	IEEE 802.11n (2.4GHz): 130.0 Mbps³ IEEE 802.11n (5GHz): 24 Mbps³ IEEE 802.11n (5GHz): 270.0 Mbps³ IEEE 802.11ac (5GHz): 780Mbps³ IEEE 802.11ac (5GHz): 780Mbps³ Wi-Fi Direct  Oft)  - 80% humidity, No condensation)  - 80% humidity, No condensation)  - high altitude mode)
Supported Speed For E  Supported Mode Interactive Specificati Interactive Unit Technology Input Devices  Connection To Con Calibration  Functions Touch Unit Maximum Dimensic Weight Operating Temperatur Single Use Multi-projection Use Direct Power On / Off Start-Up Period Cool Down Period Air Filter Power Consumption I Lamp On (Normal / Eco Standby (Network On / C)	ion  Interactive Pen Fingers nputer  on (D x W x H)  re  Type Maintenance Cycle (220 - 240V) ) Off)	N/A  Infrared  Digital Pen (Easy Interactive Pen 1 & 2)  Yes (Up to 6 Fingers)  USB, Network Pen: Auto / Manual (25 Points) Finger: Manual (16 Points) Hover, Right Click, Auto Adjust Pen Area  51 x 210 x 95 mm  450g  5 - 40 °C <41 - 104 °F> (0m / 0ft to 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 95 °F> (ower 2,286m / 7,500ft) (20% 5 - 35 °C <41 - 96 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% 5 - 30 °C <41 - 86 °F> (over 1,500m / 4,921ft: wit) Yes / N/A  About 8 seconds, Warm-up Period: 30 seconds Instant Off Electrostatic Filter 10,000 hour <sup>4</sup> 100 - 240 V AC ±10%, 50/60 Hz  401W / 334W 3.0W / 0.32W	IEEE 802.11n (2.4GHz): 130.0 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 54 Mlops <sup>3</sup> IEEE 802.11n (5GHz): 270.0 Mlops <sup>3</sup> IEEE 802.11ac (5GHz): 780Mlops <sup>3</sup> IEEE 802.11ac (5GHz): 780Mlops <sup>3</sup> Wi-Fi Direct  Oft)  - 80% humidity, No condensation)  - 80% humidity, No condensation)  h high altitude mode)

Supplied Accessories

Power Cable: 4.5m USB Cable: 5m x 2, 1.8m x 1 Remote Control with Battery Attached Interactive Pens: 2 pens with AA Battery Pen Stand: 1 Setting Plate Light Curtain Unit Light Curtain Unit Bracket Pen Tip (Felt): 4 Pen Tip (Teflon): 2 Pen Tip Holder Control Pad Wireless LAN Unit (ELPAP10)

#### Stereo Mini for Control Pad **Optional Accessories**

Spare Lamp: ELPLP92

Air Filter: EL PAF45

Remote Control Cable Set: ELPKC28 (10m x 2) (for synchronization of Interactive IR)

Setting Plate: ELPMB46 Table Mount Bracket: ELPMB29 Easy Interactive Pen 1 (Orange): ELPPN05A Easy Interactive Pen 2 (Blue): ELPPN05B Replacement Hard Pen Tips: ELPPS03 (for ELPPN05) Replacement Soft Pen Tips: ELPPS04 (for ELPPN05)

EB-1450Ui / EB-1460Ui



©2017 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android is a trademark of Google Inc.

Information correct as at January 2017

- Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.
   Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.
- Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.
- When used in the general office environment (the amount of floating dust: 0.04 0.2 mg/m3). Based on the Epson's in-house test results.